



Eurodet

PRODUCTION OF DETERGENTS - CARS - INDUSTRY - COMMUNITY - HEAVY GOODS VEHICLES

ANTIRUGGINE

rev. **02**

date: **29/08/2023**

Passivating for ferrous metals

CHARACTERISTICS: Specific product to inhibit the oxidation of metals after pickling surface treatments. The passivator works on the metal with a combination of chemical and chemical-physical processes, creating a thin protective film suitable for the subsequent painting phases.



INSTRUCTIONS FOR USE: Dilute the product and brush it (spray it) on the part to be treated, leave to act for a few minutes and rinse with plenty of water we do not recommend using it on large surfaces, we recommend limited and targeted use

the product is strongly acidic therefore it is necessary to operate in favor of the wind in order to avoid splashes and the aspiration of vapours. Do not mix with other products and avoid contact with painted and enamelled surfaces. During use, use gloves and appropriate protective clothing

| PARAMETERS | VALUES | ANALYSIS METHOD |
|----------------------------|--------------------|-----------------|
| Physical appearance | liquid | |
| Smell | Characteristic | |
| Specific weight (kg/lt) | 1.13-1.17 at 20 °C | (INT1) |
| Active matter (brix scale) | NA | (INT2) |
| PH | 1 | (INT3) |
| Flammability | None | |
| Hazard symbol | GHS05 | |
| Biodegradability | Over 90% | |
| Surfactants | Non-ionic | |

This product is distributed in compliance with Legislative Decree 14.03.03 n° 65, Dir. 94/1/EEC, Dir. 67/548/EEC and subsequent amendments

SANITARY INFORMATION: In case of contact with skin and eyes, rinse thoroughly. with water. In case of ingestion, do not induce vomiting, keep the subject at rest and seek medical attention.

| DILUIZIONI / DILUTION |
|-----------------------|
| con acqua/with water |
| 1 / 10 |
| |
| |
| |
| |



GO TO THE DEDICATED CATEGORY ON OUR WEBSITE
WWW.EURODET.IT