



B 87

rev. **02**

date: **29/08/2023**

Hot degreaser in rotary tank

CHARACTERISTICS: Specific product to inhibit the oxidation of metals after pickling surface treatments. The passivator works on the metal with a combination of chemical and chemical-physical processes, creating a thin protective film suitable for the subsequent painting phases.

INSTRUCTIONS FOR USE: Dilute the product and brush it (spray it) on the part to be treated, leave to act for a few minutes and rinse with plenty of water we do not recommend using it on large surfaces, we recommend limited and targeted use



PARAMETERS	VALUES	ANALYSIS METHOD
Physical appearance	liquid	
Smell	Characteristic	
Specific weight (kg/lt)	1.13-1.17 at 20 °C	(INT1)
Active matter (brix scale)	NA	(INT2)
PH	1	(INT3)
Flammability	None	
Hazard symbol	GHS05	
Biodegradability	Over 90%	
Surfactants	Non-ionic	

This product is distributed in compliance with Legislative Decree 14.03.03 n° 65, Dir. 94/1/EEC, Dir. 67/548/EEC and subsequent amendments

SANITARY INFORMATION: In case of contact with skin and eyes, rinse thoroughly. with water. In case of ingestion, do not induce vomiting, keep the subject at rest and seek medical attention.

DILUIZIONI / DILUTION
in acqua/with water 3-5 %



GO TO THE DEDICATED CATEGORY ON OUR WEBSITE
WWW.EURODET.IT