



## SMOT

rev. **02**

date: **29/08/2023**

### Degreaser for mechanical parts

**CHARACTERISTICS:** Degreaser for mechanical parts where it eliminates oily residues, grease and smog. thanks to its particular surfactants. It can also be used at high temperatures without damaging gaskets, metal and plastic paints.

**INSTRUCTIONS FOR USE:** spray the solution evenly from bottom to top, then rinse with a pressure washer.



PARAMETERS	VALUES	ANALYSIS METHOD
Physical appearance	Liquid	
Smell	Characteristic	
Specific weight (kg/lt)	1.08-1.10 at 20 °C	(INT1)
Active matter (brix scale)	18- 20 °Bx at 20 °C	(INT2)
PH	12	(INT3)
Flammability	None	
Hazard symbol	GHS05	
Biodegradability	Over 90%	
Surfactants	Anionic and non-ionic	

This product is distributed in compliance with Legislative Decree 14.03.03 n° 65, Dir. 94/1/EEC, Dir. 67/548/EEC and subsequent amendments

**SANITARY INFORMATION:** In case of contact with skin and eyes, rinse thoroughly. with water. In case of ingestion, do not induce vomiting, keep the subject at rest and seek medical attention.

DILUZIONI / DILUTION	
con trigger / with trigger	1 : 2 / 5
con pennello / with brush	1 : 20 / 30



GO TO THE DEDICATED CATEGORY ON OUR WEBSITE  
[WWW.EURODET.IT](http://WWW.EURODET.IT)