



Eurodet

PRODUCTION OF DETERGENTS - CARS - INDUSTRY - COMMUNITY - HEAVY GOODS VEHICLES

SOLEX

rev.

02

date:

29/08/2023

Manual wax

CHARACTERISTICS: Deperlante wax for manual use formulated with water-repellent substances which ensure rapid breaking of the film of water on the car. It also leaves the paint shiny.

INSTRUCTIONS FOR USE: Distribute the diluted product evenly on the bodywork.



PARAMETERS	VALUES	ANALYSIS METHOD
Physical appearance	Liquid	
Smell	Caratteristico	
Specific weight (kg/lt)	0.98-0.99 at 20 °C	(INT1)
Active matter (brix scale)	5-7 °Bx at 20 °C	(INT2)
pH	5	(INT3)
Flammability	None	
Hazard symbol	GHS05 GHS09	
Biodegradability	Over 90%	
Surfactants	Cationic and non-ionic	

This product is distributed in compliance with Legislative Decree 14.03.03 n° 65, Dir. 94/1/EEC, Dir. 67/548/EEC and subsequent amendments

SANITARY INFORMATION: In case of contact with skin and eyes, rinse thoroughly. with water. In case of ingestion, do not induce vomiting, keep the subject at rest and seek medical attention.

DILUZIONI / DILUTION

con nebulizzatore / with nebulizer
1:100 / 300
 per 10 litri acqua manualmente
10 - 20 ml
 for 10 liters of water by hand
 10 - 20 ml



GO TO THE DEDICATED CATEGORY ON OUR WEBSITE
WWW.EURODET.IT